













































Hilook-NVR				
Items	Description	User Price		
1	<b>IPC-B120</b> 1/2.8" progressive scan CMOS-1920 × 1080@30fps -2.8 mm fixed lens- H.264+, H.264- Color: 0.01 Lux @(F1.2, AGC ON), 0.028 Lux @(F2.0, AGC ON)-BLC/3D DNR-IP67-Digital WDR	IRR 16,300,000		
2	<b>IPC-B120H</b> 2MP-1/2.8" Progressive CMOS, ICR, 1920x1080:25fps(P)/30fps(N), H.265+/H265/H.264+&H.264, 3D DNR, -2.8/4/6mm fixed lens BLC, DC12V & PoE,-up to 30m IR-Support mobile monitoring via Hik-Connect *power supply no included-DWDR- Front Cover: Metal-Back Cover & Bracket: Plastic-IP67	IRR 19,300,000		
	<b>IPC-B121H</b> 1/2.8" progressive scan CMOS 3D DNR 1920 × 1080@30fps Up to 30 m IR range 2.8 mm/4 mm fixed lens IP67, DWDR, H265	IRR 19,800,000		
3	<b>IPC-B140H</b> 4MP- 1/3" Progressive CMOS, ICR, 2560x1440:20fps(P)/(N), H.265+/H265/H.264+&H.264, 3D DNR, BLC, DWDR - DC12V & PoE, 2.8/4/6mm fixed lens, Support mobile monitoring via Hik-up to 30m IR, Connc *power supply no included-Front Cover: Metal Back Cover & Bracket: Plastic-IP67	IRR 23,500,000		
4	<b>IPC-B220</b> 1/2.8" progressive scan CMOS - Up to 2.0 megapixel high resolution-H264- 4 mm Lens-Up to 30 m IR distance-Dual stream-DWDR-3D DNR (Digital Noise Reduction)-BLC-IP67- Mobile monitoring via mobile application	IRR 16,600,000		
5	<b>IPC-B220-D</b> 1/2.8" progressive scan CMOS - Up to 2.0 megapixel high resolution-H264- 4 mm Lens-Up to 30 m IR distance-Dual stream-DWDR-3D DNR (Digital Noise Reduction)-BLC-IP67- Mobile monitoring via mobile application- D model only support 12VDC power supply	IRR 14,800,000		
6	<b>IPC-T120</b> 2MP-1/2.8" Progressive CMOS, ICR, 1920x1080:25fps(P)/30fps(N), DWDR -H.264+&H.264- 2.8/4/6mm fixed lens- BLC, - DC12V & PoE -,up to 10m IR- Support mobile monitoring via Hik-Connect *power supply no included-Eyeball:Plastic-Cover: Plastic-Indoor-ip67	IRR 12,800,000		
7	<b>IPC-T120-D</b> 1/2.8" progressive scan CMOS-Up to 2.0 megapixel -2.8 mm fixed focal lens-H264+ - 10 m IR range-Dual stream-DWDR-3D DNR (Digital Noise Reduction)- Mobile monitoring via mobile application-IP 67- D model only support 12VDC power supply	IRR 9,950,000		
8	<b>IPC-T220-H</b> 2MP-1/2.8" Progressive CMOS, ICR, 1920x1080:25fps(P)/30fps(N), H.265+/H265/H.264+&H.264, 3D DNRDWDR, BLC, DC12V & PoE,-up to 30m IR-Support mobile monitoring via HikConnect *power supply no included2.8/4/6mm fixed lens- Eyeball: MetalCover: Plastic-IP67	IRR 15,500,000		
	<b>IPC-T220</b> 1/2.8" progressive scan CMOS BLC/3D DNR,1920 × 1080@30fps,IP67 2.8, 4, 6 mm fixed lens,Digital WDR,H.264+, H.264 Color: 0.01 Lux @(F1.2, AGC ON), 0.028 Lux @(F2.0, AGC ON);	IRR 12,800,000		
9	<b>IPC-T240H</b> 4MP-1/3" Progressive CMOS, ICR, 2560x1440:20fps(P)/(N), H.265+/H265/H.264+&H.264,up to 30m IR- 3D DNR-DWDR, BLC, DC12V & PoE- 2.8/4/6mm fixed lens,-Support mobile monitoring via Hik-Connec *power supply no included-Eyeball: Metal-Cover: Plastic- IP67	IRR 18,500,000		
10	<b>IPC-D120</b> 1/2.8" progressive scan CMOS-2 MP-1920 × 1080@30fps-2.8mm fixed lens-H.264+, H.264- Color: 0.01 Lux @(F1.2, AGC ON), 0.028 Lux @(F2.0, AGC ON)-BLC/3D DNR-IP67-Digital WDR- IK 10	IRR 15,800,000		
11	<b>IPC-D120H</b> 2MP-1/2.8" Progressive CMOS, ICR, 1920x1080:25fps(P)/30fps(N), H.265+/H265/H.264+&H.264, 3D DNR, -2.8/4/6mm fixed lens- BLC, DC12V & PoE,DWDR- Support mobile monitoring via Hik-Connect *power supply no included-up to 30m IR- Base: Metal-Cover: Plastic-IP67, IK10	IRR 18,500,000		
12	<b>IPC-D140H</b> 4.0 MP IR NetworkDome Camera,1/3" progressive scan CMOS, 3D DNR (Digital Noise Reduction), 2560 × 1440@20fps Up to 30 m IR range, 2.8 mm/4 mm/6 mm fixed lens,PoE (Power over Ethernet),H.265+, H.265, H.264+, H.264 IP67, IK10, Dual stream, 120 dB WDR.	IRR 19,800,000		
13	<b>Vari-Focal Series</b>			
14	<b>IPC-B620H-V</b> 2MP-1/2.8" Progressive CMOS, ICR, 1920x1080:25fps(P)/30fps(N),H.265+/H265/H.264+&H.264, 3D DNR , DWDR- BLC, DC12V & PoE, TF card slot,up to 30m IR-Support mobile monitoring via Hik-Connect *power supply no included-2.8-12mm vari-focal lens-Body&Bracket: Metal-SunShield: Plastic-IP67	IRR 35,500,000		

15	IPC-B620H-Z	2MP-1/2.8" Progressive CMOS, ICR, 1920x1080:25fps(P)/30fps(N), H.265+/H.264+&H.264, 3D DNR, BLC, -up to 30m IR-DC12V & PoE, -D-WDR- TF card slot, -Support mobile monitoring via Hik-Connect *power supply no included-2.8"-12mm motorized vari-focal lens-Body&Bracket: Metal-SunShield: Plastic-IP67	IRR 35,600,000	
16	IPC-B640H-V	4MP- 1/3" Progressive CMOS, ICR, 2560x1440:20fps(P)/(N), H.265+/H.265/H.264+&H.264, 3D DNR, BLC, up to 30m IR- DC12V & PoE, TF card slot, WDR- Support mobile monitoring via Hik-Connect *power supply no included-2.8"-12mm vari-focal lens-Body&Bracket: Metal-SunShield: Plastic-IP67	IRR 39,200,000	
17	IPC-B640H-Z	4MP- 1/3" Progressive CMOS, ICR, 2560x1440:20fps(P)/(N), H.265+/H.265/H.264+&H.264, 3D DNR, BLC, up to 30m IR- DC12V & PoE, TF card slot, -WDR- Support mobile monitoring via Hik-Connect *power supply no included-2.8"-12mm motorized vari-focal lens-Body&Bracket: Metal-SunShield: Plastic-IP67	IRR 44,600,000	
18	IPC-T620-Z	2MP-1/2.8" Progressive CMOS, ICR, 1920x1080:25fps(P)/30fps(N), H.264+&H.264, 3D DNR, BLC, -WDR- up to 30m IR-DC12V & PoE, Support mobile monitoring via Hik-Connect *power supply no included-2.8"-12mm VF lens-Eyeball: MetalCover: Plastic-IP67	IRR 28,250,000	
19	IPC-D620H-V	2MP-1/2.8" Progressive CMOS, ICR, 1920x1080:25fps(P)/30fps(N), H.265+/H.265/H.264+&H.264, D-WDR- 3D DNR, BLC, 2.8"-12mm varifocal lens - DC12V & PoE, TF card slot, -up to 30m IR-- Support mobile monitoring via Hik-Connect *power supply no included -Full Metal-IP67, IK10	IRR 23,700,000	
20	IPC-D620H-Z	1/2.8" progressive scan CMOS-2 MP-1920 x 1080@30fps- 2.8 mm to 12 mm manual/motorized (with -Z) vari-focal lens- H.265+, H.265, H.264+, H.264-Dual stream- D-WDR -3D DNR (Digital Noise Reduction)-Up to 30 m IR range-PoE (Power over Ethernet)- IP67, IK10	IRR 32,600,000	
21	IPC-D640H-V	4MP-1/3" Progressive CMOS, ICR, 2560x1440:20fps(P)/(N), H.265+/H.265/H.264+&H.264, WDR, 3D DNR, BLC, up to 30m IR- DC12V & PoE, TF card slot--2.8"-12mm vari-focal lens- Support mobile monitoring via Hik-Connect *power supply no included - Full Metal-IP67, IK10	IRR 29,300,000	
22	IPC-D640H-Z	4MP-1/3" Progressive CMOS, ICR, 2560x1440:20fps(P)/(N), H.265+/H.265/H.264+&H.264, WDR, 3D DNR, BLC, up to 30m IR- DC12V & PoE, TF card slot--2.8"-12mm vari-focal lens- Support mobile monitoring via Hik-Connect *power supply no included - Full Metal-IP67, IK10	IRR 36,600,000	
23	<b>PanoVu Mini Series IR Network PTZ Camera</b>			
24	PTZ-P332ZI-DE3	System Functions 1 3-ch panoramic images in different directions and 1-ch close-up image 1 PTZ linkage Up to 10 m IR radius Panoramic Camera Three 1/2.8" progressive scan CMOS 3-ch 1920 x 1080@30fps resolution Horizontal FOV: 128.5° x 3 PTZ Camera 1/2.8" progressive scan CMOS Up to 1920 x 1080@30fps resolution 4x optical zoom, 8x digital zoom	ناموجود	
25	<b>IP PTZ Camera</b>			
26	PTZ-N2204I-DE3	1/2.8" progressive scan CMOS @p to 1920 x 1080@30fps resolution Min. illumination: Color: 0.005 Lux @(F1.6, AGC ON) B/W: 0.001 Lux @(F1.6, AGC ON) 0 Lux with IR 15x optical zoom, 16x digital zoom 120dB WDR, 3D DNR, HLC, EIS, Regional Exposure, Regional Focus 2 VDC & PoE @p to 20 m IR distance IK10, IP66 Support H.265+/H.265 video compression	ناموجود	
27	PTZ-N2404I-DE3	1/3" progressive scan CMOS @p to 2560 x 1440@25fps resolution Min. illumination: Color: 0.005 Lux @(F1.6, AGC ON) B/W: 0.001 Lux @(F1.6, AGC ON) 0 Lux with IR 15x optical zoom, 16x digital zoom 120dB WDR, 3D DNR, HLC, EIS, Regional Exposure, Regional Focus 2 VDC & PoE @p to 20 m IR distance IK10, IP66 Support H.265+/H.265 video compression	ناموجود	
28	PTZ-N4215-DE3	1/2.8" progressive scan CMOS Up to 1920 x 1080 resolution Min. illumination: Color: 0.005 Lux @(F1.6, AGC ON) B/W: 0.001 Lux @(F1.6, AGC ON) 0 Lux with IR 15x optical zoom, 16x digital zoom 120dB WDR, 3D DNR, HLC, BLC 12 VDC & PoE+ (802.3at, class4) Support H.265+/H.265 video compression Up to 24 programmable privacy masks Support ROI	ناموجود	
29	PTZ-N4215I-DE	1/2.8" progressive scan CMOS Up to 1920 x 1080 resolution Min. illumination: Color: 0.005 Lux @(F1.6, AGC ON) B/W: 0.001 Lux @(F1.6, AGC ON) 0 Lux with IR Up to 100 m IR distance 15x optical zoom, 16x digital zoom 120dB WDR, 3D DNR, HLC, Smart IR 12 VDC & PoE+ (802.3at, class4) Support H.265+/H.265 video compression Up to 24 programmable privacy masks Support ROI	ناموجود	

30	PTZ-N4225I-DE	1/2.8" progressive scan CMOSUp to 1920 × 1080 resolution Min. illumination: Color: 0.005 Lux @(F1.6, AGC ON) B/W: 0.001 Lux @(F1.6, AGC ON) 0 Lux with IRUp to 100 m IR distance 25× optical zoom, 16× digital zoom120dB WDR, 3D DNR, HLC, BLC, Smart IR 12 VDC & PoE+ (802.3at, class4)Support H.265+/H.265 video compression Up to 24 programmable privacy masksSupport ROI	ناموجود	
31	PTZ-N5225I-AE	1/2.8" progressive scan CMOSUp to 1920 × 1080 resolution Min. illumination: Color: 0.005 Lux @(F1.6, AGC ON) B/W: 0.001 Lux @(F1.6, AGC ON) 0 Lux with IR Up to 150 m IR distance 25× optical zoom, 16× digital zoom120dB WDR, 3D DNR, HLC, BLC, Smart IR 24 VAC & PoE+ (802.3at, class4)Support H.265+/H.265 video compression Up to 24 programmable privacy masksSupport ROI Support smart detection	ناموجود	
<b>Network Video Recorder</b>				
33	NVR-104-B	Full channel recording at up to 4 MP resolution-40Mbps Bit Rate Input Max (up to 4-ch IP video),Output Bandwidth 40Mbps- H.264, 1 SATA interface 6TB, mini 1U case(Plastic)-HDMI Output 1, up to 1080P-Decoding Capability-2-ch@ 4MP-4-ch@1080p	IRR 12,600,000	
35	NVR-108-B	Full channel recording at up to 4 MP resolution-60Mbps Bit Rate Input -Max (up to 8-ch IP video),Output Bandwidth 40Mbps- H.264, 1 SATA interface 6TB, mini 1U case(Plastic)-HDMI Output 1, up to 1080P-Decoding Capability-2-ch@4 MP, 4-ch@1080p	IRR 15,600,000	
37	NVR-104MH-C	Recording at up to 8 MP resolution40Mbps Bit Rate -Input Max (up to 4-ch IP video UP to 8MP), Output Bandwidth 80Mbps- H.265, 1 SATA (6TB)interface, standalone 1U 315 case(Metal)-HDMI Output 1CH 4K, --Decoding Capability 1-ch @ 8 MP / 4-ch @ 1080p	IRR 20,400,000	
	NVR-104MH-D	Up to 4 channel IP cameras can be connected Supports decoding H.265+/H.265/H.264+/H.264 multiple video formats Up to 4-ch @ 1080p decoding capacity 1 HDD for continuous video recording.	IRR 15,600,000	
	NVR-104MH-D/4P	Up to 4 channel IP cameras can be connected Plug & Play with 4 Power-over-Ethernet (PoE) interfaces Supports decoding H.265+/H.265/H.264+/H.264 multiple video formats Up to 4-ch @ 1080p decoding capacity 1 HDD for continuous video recording	IRR 28,400,000	
38	NVR-104MH-C/4P	Recording at up to 8 MP resolution-40Mbps Bit Rate Input- Max (up to 4-ch IP video UP to 8 MP), Output Bandwidth 80Mbps- H.265, 1 SATA(6TB) interface, 4 independent PoE network interfaces, 1U 315 case(Metal)-HDMI Output 1ch 4K-Decoding Capability 1-ch @ 8 MP 4-ch @ 1080P	IRR 28,400,000	
39	NVR-108MH-C	Recording at up to 8 MP resolution-80Mbps Bit Rate Input- Max (up to 8-ch IP video UP to 8 MP),Output Bandwidth 80Mbps- H.265, 1 SATA interface(6TB), standalone 1U 315 case(Metal)-HDMI Output 1CH 4K,Decoding Capability: -1-ch @ 8 MP / 4-ch @ 1080p	IRR 27,400,000	
43	NVR-108MH-D	IP video input 8ch, Incoming bandwidth 60 Mbps Outgoing,bandwidth 60 Mbps, Recording resolution 4 MP/3 MP/1080p/UXGA /720p/VGA/4CIF/DCIF/ 2CIF/CIF/QCIF, H.265+/H.265/ H.264+/H.264, 1 SATA interface,Capacity Up to 6TB capacity for each disk,	IRR 21,600,000	
40	NVR-208MH-C	Recording at up to 8 MP resolution-80Mbps Bit Rate Input- Max (up to 8-ch IP video UP to 8 MP),Output Bandwidth 80Mbps- H.265, 2 SATA interface(6TB), standalone 1U 315 case(Metal)-HDMI Output 1CH 4K,Decoding Capability: -1-ch @ 8 MP / 4-ch @ 1080p	IRR 29,400,000	
41	NVR-108M-C/8P	Recording at up to 8 MP resolution-80Mbps Bit Rate Input- Max (up to 8-ch IP video UP to 8mp),Output Bandwidth 80Mbps- H.265, 1 SATA interface(6 TB),8 independent PoE network interfaces, standalone 1U 315 case(Metal)-HDMI Output 1ch 4k, -Decoding Capability:1-ch @ 8 MP / 4-ch @ 1080p	IRR 49,500,000	
42	NVR-108M-D/8P	IP video input 8ch, Incoming bandwidth 60 Mbps Outgoing,bandwidth 60 Mbps, Recording resolution 4 MP/3 MP/1080p/UXGA /720p/VGA/4CIF/DCIF/ 2CIF/CIF/QCIF, H.265+/H.265/ H.264+/H.264, 1 SATA interface,Capacity Up to 6TB capacity for each disk,	IRR 44,000,000	
44	NVR-116MH-C	Recording at up to 8 MP resolution-160Mbps Bit Rate Input- Max (up to 16-ch IP video UP to 8MP),Output Bandwidth 80Mbps- H.265, 1 SATA interface(6TB), standalone 1U 315 case(Metal)-HDMI Output 1CH 4K, Decoding Capability: 1-ch @ 8 MP / 4-ch @ 1080p	IRR 31,400,000	
45	NVR-216MH-C	Recording at up to 8 MP resolution-160Mbps Bit Rate Input- Max (up to 16-ch IP video),Output Bandwidth 80Mbps- H.265-2,SATA up to 6TB per HDD interface,standalone 1U 385 case(Metal)-HDMI Output1 ch 4k--Decoding Capability: 1-ch @ 8 MP / 4-ch @ 1080p	IRR 35,400,000	
46	NVR-216MH-C/16P	Recording at up to 8 MP resolution-160Mbps Bit Rate Input- Max (up to 16-ch IP video),Output Bandwidth 80Mbps- H.265, 2 SATA ( up to 6TB per HDD) interface,16 independent PoE network interfaces, standalone 1U 385 case(Metal)-HDMI Output1 ch 4k, Decoding Capability 1-ch @ 8 MP / 4-ch @ 1080p	IRR 76,500,000	

D.D.C PERSIA

TelFax : 98 21 88 54 18 00

98 21 88 55 55 58

98 21 88 10 20 01 - 5

[www.ddcpersia.com](http://www.ddcpersia.com)

[info@ddcpersia.com](mailto:info@ddcpersia.com)