



180° Panoramic H265+ Mini Bullet Network Camera



FCS-5094 (5MP)

Level One




180° Panoramic H265+ Mini Bullet Network Camera

Level One		180° Panoramic H265+ Mini Bullet Network Camera	
Camera	Model	FCS-5094 (5MP)	
	image Sensor	1/2.8" Progressive Scan CMOS	
	min.illumination	Color: 0.005Lux@F1.2 Color: 0.008Lux@F2.0 B/W : 0Lux with IR on	
	WDR	120dB Super WDR	
	shutter Time	1/100000s~1s	
	IR distance	Up to 15m	
	Lens	1.68mm@F2.0	
	Mount	M12	
	field of view	H180°/V95°	
	day&night	Day/Night/Auto/Customize/Schedule	
	S/N	55dB	
Video	Max resolution	2592x1944	
	primary stream	30fps@(2592x1944)(Original),30fps@(2560x1440, 1920x1080, 1280x720)	
	Secondary stream	30fps(640x480, 640x360, 320x240)	
	tertiary stream	30fps@(1920x1080, 1280x720, 704x576, 640x480, 640x360, 320x240, 320x192, 320x180)	
	Video Compression	H.265+/H.265(HEVC)/H.264+/H.264	
	Video Bit Rate	16Kbps~16Mbps(CBR/VBR Adjustable)	
	Privacy Masking	Up to 24 areas	
	ROI	Up to 8 areas	
Interface	Image Setting	Brightness/Contrast/Saturation/Sharpness	
	Ethernet	1*RJ45 10M/100M Ethernet Port	
	Audio	Built-in Microphone	
Network	Network Storage	NAS(Support NFS, SMB/CIFS), ANR	
	Protocol	IPv4/IPv6, ARP, TCP, UDP, RTCP, RTP, RTSP, RTMP, HTTP, HTTPS, DNS, DDNS, DHCP, FTP, NTP, SMTP, SNMP, UPnP, Bonjour, SIP, PPPoE, VLAN, 802.1x, QoS, IGMP, ICMP, SSL	
Audio	Audio Compression	G.711/AAC/G.722/G.726	
	Audio Sampling Rate	8/16/32/48KHz	
	Audio Bit Rate	16~256kbps	
System	Storage	Support microSD/SDHC/SDXC Card Local Storage, up to 256G Heat Map, BLC, HLC, 2D DNR, 3D DNR,	
	Advanced Function	Defog, AWB, EIS, IP Address Filtering, AGC, Anti-flicker, Corridor Mode, Deblur, Watermark	
	SIP/VoIP Support	Yes, Voice & Video-over-IP	
	Event Trigger	Motion Detection, Network Disconnection, Audio Alarm, etc.	
	Event Action	FTP Upload, SMTP Upload, SD Card Record, SIP Phone, HTTP Notification, etc.	
	Video Analysis	Region Entrance, Region Exiting, Advanced Motion Detection, Tamper Detection, Line Crossing, Loitering, Human Detection, People Counting, Object Left, Object Removed	
	System Compatibility	ONVIF Profile G & Q & S & T, API	



H265+ 23X Mini PTZ Dome Network Camera



Level One		 H265+ 23X Mini PTZ Dome Network Camera
Interface	Model	FCS-4051 (2MP)
	Ethernet	1*RJ45 10M/100M Ethernet Port
	Audio I/O	1\1
	Alarm I/O	1\1
Network	Network Storage	NAS(Support NFS, SMB/CIFS), ANR
	Protocol	IPv4/IPv6, ARP, TCP, UDP, RTCP, RTP, RTSP, RTMP, HTTP, HTTPS, DNS, DDNS, DHCP, FTP, NTP, SMTP, SNMP, UPnP, Bonjour, SIP, PPPoE, VLAN, 802.1x, QoS, IGMP, ICMP, SSL
Audio	Audio Compression	G.711/AAC/G.722/G.726
	Audio Sampling Rate	8/16/32/44.1/48KHz
	Audio Bit Rate	16~256kbps
	Two-way Audio	Support
System	Storage	Support microSD/SDHC/SDXC Card Local Storage, up to 256G BLC, HLC, 2D DNR, 3D DNR, Defog, AWB, EIS, IP Address Filtering
	Advanced Function	AGC, Anti-flicker, Corridor Mode, Deblur, Watermark
	SIP/VoIP Support	Yes, Voice & Video-over-IP
	Event Trigger	Motion Detection, Network Disconnection, Audio Alarm, External Input, etc.
	Event Action	FTP Upload, SMTP Upload, SD Card Record, External Output, SIP Phone, HTTP Notification, etc.
	Video Analysis	Region Entrance, Region Exiting, Advanced Motion Detection, Tamper Detection, Line Crossing, Loitering, Human Detection, People Counting, Object Left, Object Removed
General	System Compatibility	ONVIF Profile G & Q & S & T, API
	Working Temperature	(- 40) (+60)°C
	Working Humidity	0~90%(Non-condensing)
	Power Supply	PoE (802.3af) / DC 12V±10%
	Power Consumption	10W MAX/17W MAX (With IR on)
	Housing	Vandal-proof IK10-rated Metal Housing
	Weather Proof	Up to IP66-rated for Weather-resistant Performance
	Weight	2Kg
	Surge Protection	4KV
	Dimensions	Φ183mmX174.8mm
Warranty	2/5 Years	

Structure Diagrams

